

# Transmitters and receivers



Three fundamental characteristics distinguish V2 transmitters and receivers from traditional remote control devices:

- **installer protection**
- **user protection**
- **high level of flexibility**

They protect the installer because they guarantee exclusive administration of the systems being automated. Indeed, each installer is given a customized code with which they, and only they, can work on the installed systems, and only they can provide additional spare transmitters for the same system.

They protect the user because they allow remote control of both shared access with other users and personalised access for exclusive use. Indeed, the use of factory-set serialised transmitters (or programmed by the installer) each with a different code, allows copy-proof, personal identification of each individual user. In the case of loss of the original transmitter, the installer will cancel the code attributed originally to the user and assign them a new code in place of the lost one.

High level of flexibility because the vast range of receivers available, capable of storing between 83 to 1008 codes from different transmitters, allow the management and expansion of small and large systems.

## PMR

Wall-mounted radio transmitter control for one or more screens or shades



- Available in 2 channel and 4 channel versions
- Operating frequency 433.92 MHz
- Working range of up to 20 m in closed environments, passing through even 2 main walls, and 200 m in the open
- Option to automatically prolong transmission for 3 seconds
- Automatic 3 time repetition of the last command executed



**PMR 4 channel**  
(Item code 10K004)



**PMR 2 channel**  
(Item code 10K001)