











Presto, steel

Approved models / Technical specifications

		RS			G30		
Resistance class		Presto RS-1	Presto RS-2	Presto wall units	Presto G30	Presto G30 ²⁾	
Models	Doors and wall units with glazing						
	Doors can be combined with wall units – in any transom spacing						
	Transoms – vertical	any	any	any	any	any	
	Transoms - horizontal	any	any	any	any	any	
Unit division	Slants	-	-	•	-	•	
	Arches	-	-	•	-	•	
	Recesses	-	-	•	-	•	
	Angles	-	-	•	-	•	
	Widening	•	•	•	-	•	
Dimensions	Shell dimension (greater dimensions possible using frame variants)	Width min. - max.	610 – 1610	1610 x 3030	unlimited ¹⁾	unlimited ¹⁾	unlimited ¹⁾
		Height min. - max.	1745 – 2835	1745 x 2835	unlimited ¹⁾	≤ 3515	≤ 5000 10015 bei W ≤ 1030
		Height (with fanlight)	unlimited ¹⁾	unlimited ¹⁾	-	-	-
	Frame outer dimension (greater dimensions possible using frame variants)	Width min. - max.	580 – 1580	1580 x 3000	unlimited ¹⁾	unlimited ¹⁾	unlimited ¹⁾
		Height min. - max.	1730 – 2820	1730 x 2820	unlimited ¹⁾	≤ 3500	≤ 5000 10015 bei W ≤ 1000
		Height (with fanlight)	unlimited ¹⁾	unlimited ¹⁾	-	-	-
Clear passage at 180° opening	Width min. - max.	440 – 1440	1440 x 2860	-	-	-	
	Height min. - max.	1660 – 2750	1660 x 2750	-	-	-	
Door leaf	Structural depth	50	50	50	50	50	
	View	130	130 / 150	70 / 90	70 / 90	70 / 90	
	Base height	50, 70 – 420	50, 70 – 420	50, 70 – 420	70	70	
	Transom width without glass strip / rebate vertically or horizontally	10, 20, 30, 50, 70, 90 – 400	10, 20, 30, 50, 70, 90 – 400	10, 20, 30, 50, 70, 90 – 400	20, 30, 50, 70, 90	20, 30, 50, 70, 90	
Walls	Masonry	≥ 115	≥ 115	≥ 115	≥ 115	≥ 115	
	Concrete	≥ 100	≥ 100	≥ 100	≥ 100	≥ 100	
	Foam mortar	≥ 150	≥ 150	≥ 150	-	≥ 150	
	Partition walls	≥ 100	≥ 100	≥ 100	≥ 100 ³⁾	≥ 100	
	Door / glazing combination	•	•	•	-	-	
	Z-frames	•	•	-	-	-	
	Steel and wood supports / bearers (with G30 in F30 version)		•	•	•	- •	
Fillings	Glass of choice, from 5 mm (W x H max.)	Door size	Door size	unlimited ¹⁾	-	-	
	G30-Glass of choice (W x H max.)	•	•	•	1000 x 2000 2000 x 1000	-	
	Pyran S (G30) (W x H max.)	•	•	•	1000 x 2000 2000 x 1000	1600 x 3000 3000 x 1600	
	Panelling	•	•	•	-	•	
	Glass / panelling	•	•	•	-	•	
	Glass use	Wet glazing	•	•	•	•	•
	Dry glazing	•	•	•	-	-	
Design variants	with fanlight & side part	FOD height	unlimited ¹⁾	unlimited ¹⁾	-	-	
	with fanlight	FOD height	unlimited ¹⁾	unlimited ¹⁾	-	-	
	with side part	FOD width	unlimited ¹⁾	unlimited ¹⁾	-	-	
Test certificate- / Approval numbers		P12000403-01	P12000403-02	-	Z-19.14-508	Z-19.14-1524	

¹⁾ in keeping with static requirement

²⁾ only to be used with Pyran glass

³⁾ only with a side connection

• possible – not possible